



RUBBER COATED MAGNET WITH THREADED ROD

| REFERENCES | Dimensions [mm] | | | | | Sliding resistance* [kg] | Holding force* [kg] | Weight [g] | Color |
|-----------------|-----------------|-----|------|----|----|--------------------------|---------------------|------------|-------|
| | D | H | L | d | M | | | | |
| 2402AC5Z | 22 | 6 | 11,5 | 8 | M4 | 1,5 | 3,5 | 13 | Black |
| 2402AB5Z | 22 | 6 | 11,5 | 8 | M4 | 1,5 | 3,5 | 13 | White |
| 2406AC5Z | 43 | 6 | 10,5 | 8 | M4 | 3 | 10 | 30 | Black |
| 2406AB5Z | 43 | 6 | 10,6 | 8 | M4 | 3 | 10 | 30 | White |
| 2404AC5Z | 66 | 8,5 | 15 | 10 | M5 | 8 | 25 | 105 | Black |
| 2404AB5Z | 66 | 8,5 | 15 | 10 | M5 | 8 | 25 | 105 | White |
| 2409AC5Z | 88 | 8,5 | 17 | 12 | M8 | 12 | 55 | 192 | Black |
| 2409AB5Z | 88 | 8,5 | 17 | 12 | M8 | 12 | 55 | 192 | White |

*Indicative average value at room temperature